MATERIAL SAFETY DATA SHEET

ULTRA SEAL® OBM

Trade Name: ULTRA SEAL® OBM Revision Date: 4/03/2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: ULTRA SEAL® OBM Chemical Family: Cellulose

Product Use: Oil well drilling fluid additive, seepage loss

control/differential sticking prevention and lost circulation material.

Packaging: 11.36 kg Bags - 48 Bags Per Pallet Emergency Telephone (24 Hour): +1.337.984.0471

Supplied by: M&D Industries of Louisiana, Inc. P.O. Box 82094 Lafayette, La 70598

Telephone Number: +1.337.984.0471 Contact Person: Robert Copeland

HMIS Rating

Health: 1 * Flammability: 1 Physical Hazard: 0 PPE: E

HMIS Key: 4=Severe, 3=Serious, 2=Moderate, 1 =Slight, O=Minimal Hazard. *Chronic Effects - See Section 11. See Section 8 for Personal

Protective Equipment recommendations.

2.COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredient</u>	CAS NO:	<u>WT%</u>	Ingredient Comments
Cellulose	9004-34-6	50	N/A
Proprietary		50	N/A

3. HAZARDS IDENTIFICATION

Emergency Overview: Caution! May cause eye, skin, and respiratory tract irritation. Long-term inhalation of particulates may cause lung damage, cancer hazard. Contains crystalline silica, which may cause lung cancer.

WHMIS Class: D2A

Physical: Odor: Mild (Very Faint) Color: Brown State: Powder, dust

Potential Health Effects: Acute Effects

Eye Contact: May cause mechanical irritation

Skin Contact: May cause mechanical irritation. Long-term contact can cause skin dryness. Inhalation: May cause mechanical irritation.

Ingestion: May cause gastric distress, nausea and vomiting if ingested.

Carcinogenicity & Chronic Effects: See Section 11 - Toxicological Information.

Routes of Exposure: Eyes. Dermal (skin) contact. Inhalation.

Target Organs: Eyes. Skin. Respiratory System.

4. FIRST AID MEASURES

Eye Contact: Promptly wash eyes with lots of water while lifting eyelids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin Contact: Wash skin thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if an discomfort continues.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Dilute with 2 - 3 glasses of water or milk, if conscious. Never give anything by mouth to an unconscious person. If signs of irritation o toxicity occur seek medical attention.

<u>MATERIAL SAFETY DATA SHEET</u>

Trade Name: ULTRA SEAL® OBM

Revision Date: 4/03/2013

Page 2 of 5

5.FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: F (C): Not applicable

Flammable Limits in Air - Lower (%): Not applicable Flammable Limits in Air - Upper (%): Not applicable

Auto-ignition Temperature: F(C) Not applicable Flammability Class: Not applicable

Other Flammable Properties: Particulate may accumulate static electricity. Dusts at sufficient concentrations can form explosive mixtures with

air.

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Protection Of Fire Fighters:

Special Fire Fighting Procedures: Do not enter fire area without proper personal protective equipment; including NIOSH/MSHA approved selfcontained breathing apparatus. Evacuate area and fight fire from a safe distance. Water spray may be used to keep fire-exposed containers cool. Keep water run off out of sewers and waterways.

Hazardous Combustion Products: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment identified in Section 8.

Spill Procedures: Evacuate surrounding area, if necessary. Wet product may create a slipping hazard. Contain spilled material. Avoid the generation of dust. Sweep, vacuum, or shovel and place into closable container for disposal.

Environmental Precautions: Do not allow entering sewer or surface and subsurface waters. Waste must be disposed of in accordance with federal, state and local laws.

7.HANDLING AND STORAGE

Handling: Put on appropriate personal protective equipment. Avoid contact with skin and eyes. Avoid generating or breathing dust. Product is slippery if wet. Use only in a well ventilated area. Wash contacted areas thoroughly after handling.

Storage: Store in dry, well-ventilated area. Keep container closed. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Exposure Ellints						
Ingredient	CAS NO:	Wt. %	ACGIH TLV	OSHA PEL	Other	Notes
			TWA	TWA		
Cellulose	9004-34-6	50	10 mg/m3	15 mg/m3 None (Total); mg/m3 (Respirable)	5	
Proprietary		50	3 mg/m3	5 mg/m3		

Notes:

(R) Respirable fraction (ACGIH);

Table Z-3: PEL for Mineral Dusts containing crystalline silica are 10 mg/m3/ (%SiO2+2) for quartz and 1/2 the calculated quartz value for cristobalite and tridymite.

Engineering Controls: Use appropriate engineering controls such as, exhaust ventilation and process enclosure, to ensure air contamination and keep workers exposure below the applicable limits.

<u>MATERIAL SAFETY DATA SHEET</u>

Trade Name: ULTRA SEAL® OBM Revision Date: 4/03/2013

Page 3 of 5

Personal Protection Equipment

Eye/Face Protection: Dust resistant safety goggles.

Skin Protection: Wear appropriate clothing to prevent repeated or prolonged skin contact.

Chemical resistant gloves recommended for prolonged or repeated contact. Use protective gloves made have: Neoprene. Nitrile.

Respiratory Protection: Use at least a NIOSH-approved N95 half-mask disposable or reusable particulate respirator (dusk mask). In work environments containing oil mist/aerosol, use at least NIOSH-approved P95 half-mask disposable or reusable particulate respirator. For exposure exceeding 10 x PEL use a NIOSH-approved N100 Particulate Respirator.

General Hygiene Considerations: Work clothes should be washed separately at the end of each workday. Disposable clothing should be discarded, if contaminated with product.

9.PHYSICAL AND CHEMICAL PROPERTIES

Color: Brown

Odor: Mild (or faint) Physical State: Powder, dust.

pH: Not determined.

Vapor Pressure: Not applicable Vapor Density (Air=1): Not applicable Boiling Point: Not determined

Melting/Freezing Point: Not determined

Solubility (Water): Insoluble

Specific Gravity (H2O = 1): 1.2 at 68 F (20 C)

Evaporation Rate: Not applicable Odor Threshold(s): Not determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Keep away from heat, sparks and flame.

Materials to Avoid: Oxidizers.

Hazardous Decomposition For combustion products, see Section 5.

Products:

Hazardous Polymerization: Will not occur

11.TOXICOLOGICAL INFORMATION

Component Toxicological Data

Ingredient	CAS NO:	Acute Data		
Cellulose	9004-34-6	Oral LD50: >5000 mg/kg (rat); Dermal LD50: >2000 LC50: >5800 m		

Ingredient	Component Toxicological Summary

MATERIAL SAFETY DATA SHEET

Trade Name: ULTRA SEAL® OBM

Revision Date: 4/03/2013

Page 4 of 5

Product Toxicological Information:

Long term inhalation of particulate can cause irritation, inflammation and/or permanent injury to the lungs. Illnesses such as pneumoconiosis ("dusty lung"), pulmonary fibrosis, chronic bronchitis, emphysema and bronchial asthma may develop.

12. ECOLOGICAL INFORMATION

Component Ecotoxicity Data: No data available.

Product Ecotoxicity Data: Contact M&D INDUSTRIES OF LOUISIANA, INC.

Biodegration: Not determined
Bioaccumulation: Not determined

Octanol/Water Partition: Not determined

13. DISPOSAL CONSIDERATIONS

Waste Classification: Not determined.

Waste Management: Under U.S. Environmental Protection Agency (EPA) Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user to determine at the time of disposal, whether the product meets RCRA criteria for the hazardous waste. This is because product uses, transformations, mixtures, processes, etc., may render the resulting materials hazardous. Empty containers retain residues. All labeled precautions must be observed.

Disposal Method: Recover and reclaim or recycle, if practical. Should this product become a waste, dispose of in a permitted industrial landfill Ensure that the containers are empty by the RCRA criteria prior to disposal in a permitted industrial landfill.

14. TRANSPORT INFORMATION u.s. DOT

Shipping Description: Not regulated

TDG (Canada): Not Regulated

Shipping Description: Not regulated

Hazard Class: Not regulated.

Shipping Description: Not regulated

ICAO/IATA: Not regulated

15. REGULATORY INFORMATION

U.S. Federal and State Regulations

SARA 311/312:

SARA 311/312 Hazard Categories: Delayed (chronic) health hazard

Critical Parallel Strategories. Bolayea (critorile) Health Hazara.							
INGREDIENT SARA313		CERCLA	SARA 302	CA 65	CA 65	CA 65	CA 65
		RQ	/TPQs	CANCER	DEV. TOX.	REPRO. F	REPRO. M
Cellulose	Not Listed						

State Comments: Proposition 65: This product contains chemical(s) considered by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 to cause cancer and/or reproductive toxicity. See table under U.S. Federal and State Regulations for the specific chemicals.

MATERIAL SAFETY DATA SHEET

Trade Name: ULTRA SEAL® OBM

Revision Date: 4/03/2013

Page 5 of 5

International Inventories

Ingredient CAS NO:		TSCA	DSL	NDSL	EINECS	AICS
Cellulose	9004-34-6	Listed	Listed	Not Listed	Listed	Listed
Proprietary	12002-43-6	Yes	No	No	No	Yes

Inventory Comment: "Listed" indicates the component is listed or exempt from listing on the chemical inventory .

Canadian Regulations:

Controlled Products Regulations Statement: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Class: D2A

16. OTHER INFORMATION

Disclaimer:

ALL THE RECOMMENDATIONS AND SUGGESTIONS HEREIN CONCERNING OUR PRODUCT ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE, HOWEVER, IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE SAFETY, TOXICITY, AND SUITABILITY FOR HIS OWN USE OF THE PRODUCT DESCRIBED HEREIN. SINCE THE ACTUAL USE BY OTHERS IS BEYOND OUR CONTROL, NO GUARANTEE, EXPRESSED OR IMPLIED, IS MADE BY M&D INDUSTRIES OF LOUISIANA, INC. AS TO THE EFFECTS OF SUCH USE, THE RESULTS TO BE OBTAINED, OR THE SAFETY AND TOXICITY OF THE PRODUCT NOR DOES M&D INDUSTRIES OF LOUISIANA, INC. ASSUME ANY LIABILITY ARISING OUT OF USE BY OTHERS. NOR IS THE INFORMATION HEREIN TO BE CONSIDERED AS ABSOLUTELY COMPLETE SINCE ADDITIONAL INFORMATION MAY BE NECESSARY OR DESIRABLE WHEN PARTICULAR OR EXCEPTIONAL CONDITIONS OR CIRCUMSTANCES EXIST OR BECAUSE OF APPLICABLE LAWS OR GOVERNMENT REGULATIONS.